

3/4 HP DELUXE

Easy and Fast to Install

Eco-Logic Bio Shield disposers feature Speed Master Mounting, an exclusive system that provides fast and economical installation.

Corrosion Proof

Eco-Logic Bio Shield Deluxe model carries a lifetime warranty against failure due to corrosion.

Cast Impellers

The Eco-Logic Bio Shield Deluxe model has cast stainless steel impellers which means finer grind.

Permanent Magnet Motors

Eco-Logic Bio Shield motors offer maximum torque instantly with the power to cut through potential jams.

Removable Splash Guard

All Eco-Logic Bio Shield models have a removable splash guard, ideal for easy cleaning and replacement.



BIO SHIELD (Antimicrobial)

for ODOR PROTECTION!

Disposers are treated with an antimicrobial agent molded inside providing protection against odor causing bacteria growth.

| HORSEPOWER | 3/4 HP | |
|---------------------------------------|------------------------|--|
| MOTOR SPEED RPM | 2700 RPM | |
| VOLTAGE | 100v / 120v / 220-240v | |
| AMPS | 6.5 / 6.5 / 3.25 | |
| CYCLES | 50/60 | |
| MOTOR TYPE | Permanent Magnet | |
| SPLASH GUARD | EPDM Rubber | |
| RAIN OUTLET Polycarbonate 940 | | |
| GRIND RING | Stainless Steel | |
| SWIVEL IMPELLERS Cast Stainless Steel | | |
| BALANCED TURNTABLE | Stainless Steel | |
| BALANCED ARMATURE SHAFT | Stainless Steel | |
| HOPPER | ABS | |
| DRAIN HOUSING | Thermoset polymer | |
| APPLIANCE PROTECTOR | Manual Reset | |
| SINK FLANGE | Polyamide 66 | |
| | | |



The TORQUE MASTER Grinding System is a combination of computer designed and balanced components working in unison to provide superior torque grind speed and long system life.



Silver Guard

The magnetic Silver Guard captures most metal objects before they enter into the disposer chamber. This protective feature helps prevent damage to valuable cutlery. It also helps prevent damage to the disposer as well as expensive repairs caused by metal objects falling into the disposer.

| - | APPLIANCE PROTECTOR | Manual Reset | |
|----------|--------------------------------|---|--------------|
| ı | SINK FLANGE | Polyamide 66 | • |
| ı | STOPPER | SUS304/NBR/ABS | • |
| BEARINGS | | Permanently Lubricated, Sleeve Type | • |
| 1 | SOUND SHELL | Full | • |
| ı | Dimensions | International | USA & Canada |
| ı | INDIVIDUAL SHIPPING WEIGHT | 6.8 kg | 12.11 lb |
| ı | MASTER CARTON WEIGHT (4 UNITS) | 29 kg | 55 lb |
| ı | MEASUREMENT A | 404 mm | 16" |
| ı | MEASUREMENT B | 185 mm | 7.3" |
| ı | MEASUREMENT C | 220 mm | 8.7" |
| ı | MEASUREMENT D | 140 mm White 144 mm Black Elbow | 5.7" |
| - | MEASUREMENT E | 70 mm White 100 mm Black Elbow Elbow | 3.9" |
| | LIFETIME CORROSION GUARANTEE | Yes | Yes |

©2011 Joneca Corporation, All Rights Reserved.

SS-ECO9-111



(International Market- Outside of USA & Canada)



4332 E. La Palma Avenue, Anaheim, California 92807 Telephone: 714.993.1707 Fax: 714.993.1930 Website: www.AnaheimMarketing.com Email: ContactUs@AnaheimMarketing.com

